



A Series – slow speed granulators Minimizes dust. Reduces noise.

General Description

The A series slow speed granulators feature a staggered rotor directly-driven by a geared motor. The low rotor speed reduces the noise level of the machine and creates less dust while grinding. The special design knives of the A series can be sharpened easily and do not need adjustment afterwards. The material is fed via a sound absorbing feed hopper that can be tailored to fit various applications and feeding ways. Depending on the requirements the machines can be fitted with a wide variety of hoppers, they are mounted on either low or high level base frames with matching suction bins or bag filling adapters. Quick snap fasteners and hand screws make access to the machine for cleaning and maintenance fast and easy.

Technical Machine Advantages

Direct driven staggered rotor Special knife design makes adjustment unnecessary Easy access for maintenance and cleaning Slow rotor speed creates less noise and dust Easily customizable to suit different applications

A Series		A30-40	A30-60	A30-80
Rotor diameter	(mm)	300	300	300
Rotor width	(mm)	400	600	800
Rotor speed	(rpm)	150	150	150
Drive capacity	(kW)	7.5	11	18.5
Rotor knives	(pcs)	33	48	66
Stator knives	(rows)	2	2	2
Screen size	(mm)	>5	>5	>5
	(,	_	-	-
Dimensions				
A	(mm)	1125	1125	1125
В	(mm)	400	400	400
С	(mm)	1335	1335	1340
D	(mm)	405	600	830
E	(mm)	1035	1230	1635
			_	
B				
	C			