



C Series – compact soundproofed granulators

Allows even voluminous materials to be ground.

General Description

The C compact granulators are designed with a completely soundproof enclosure resulting in an extremely quiet operation. Different rotor designs are available in widths ranging from 300 mm to 1400 mm. The completely welded cutting chamber in conjunction with the “V” type rotor design ensures dependability in operation and universal application use. While it delivers excellent sound proofing capabilities, it still offers easy and quick access to the cutting chamber during rotor and stator knife changes, servicing or screen changes. The sound dampening material used in these machines is based on the latest technological research.

Technical Machine Advantages

- Knives are adjusted outside of the machine
- Compact design
- Different rotor types available
- Soundproofed housing
- Strong tangential infeed

We reserve the right to make technical changes and measurement adjustments ver. 1.0 - 09/2014

C Series		C50-50	C50-70	C50-100	C50-140
Rotor diameter	(mm)	500	500	500	500
Rotor width	(mm)	500	700	1000	1400
Drive capacity	(kW)	30	37	45	45
Rotor knives	(rows)	3 or 5	3 or 5	3 or 5	3 or 5
Stator knives	(rows)	2	2	2	2
Screen size	(mm)	>6	>6	>6	>6
Effective working area	(mm x mm)	560 x 500	560 x 700	560 x 990	560 x 1400
Dimensions					
A	(mm)	2010	2010	2410	2410
B	(mm)	600	600	540	540
C	(mm)	1795	1795	2025	2025
D	(mm)	500	700	990	1400
E	(mm)	1380	1580	1880	2210

