



E Series – economical granulators Use as a central granulator for in-house recycling.

General Description

The completely welded cutting chamber in conjunction with the “V” type rotor design ensures dependability in operation and universal application use. The housing design offers easy and quick access to the cutting chamber during rotor and stator knife changes, servicing or screen changes.

Technical Machine Advantages

- Knives are adjusted outside of the machine
- Mobile Compact design
- Different rotor types available
- Easy accessibility
- Strong tangential infeed

We reserve the right to make technical changes and measurement adjustments ver. 1.0 - 09/2014

E50 Series		E50-50	E50-70	E50-100	E50-140
Rotor diameter	(mm)	500	500	500	500
Rotor width	(mm)	500	700	1000	1400
Drive capacity	(kW)	30	37	45	55
Rotor knives	(rows)	5	5	5	5
Stator knives	(rows)	2 or 3	2 or 3	2 or 3	2 or 3
Screen size	(mm)	>6	>6	>6	>6
Effective working area	(mm x mm)	560 x 500	560 x 700	560 x 990	560 x 1400
Dimensions					
A	(mm)	1675	1675	1900	2050
B	(mm)	580	580	580	580
C	(mm)	1840	1840	1840	1840
D	(mm)	515	715	990	1400
E	(mm)	1130	1330	1645	2000

